

Heat / Light Combination Unit 120 Volts, 14.1 amps, 60 hz.

• Grill

White, polymeric grill (flame retardant ABS UL rated 94-5V) secured in place using 2 Phillips head screws easily removed if necessary, dimensions - 17 1/8" x 9 7/8".

• Light Lens

Durable high impact polycarbonate lens. Secured in place using integral tabs.

• Blower Wheel

Heater blower wheel - one piece metal electronically balanced, 31 1/8" x 2" with 28 fins.

• Motor

Heater motor - Heavy duty, plug in 2 pole motor. Life time lubrication, thermally protected. Rated 120 volts, 60 hz., 0.90 amps., 2400 rpm.

• Heater Housing


23 gauge galvanized steel housing.
Dimensions 14 1/2" x 8 3/8" x 6 1/2".

• Heating Element

Wire coil, secured in place by ceramic "J" shaped hooks and terminated by bolt and nut in cylindrical standoffs. Housed in an all metal enclosure. Rated 1500 watts - 5120 Btu.

• Lamping Information

Main Lighting: 100 watt maximum, type A19, Medium base bulb
Night Lighting: 7 watt maximum, type C7, Candelabra base bulb



CUL - TYPE IC RATED

• Unit Mounting

Designed for ceilings insulated to R-40. Designed to mount in ceilings with at least 6.5" of clearance. The unit will mount between joists (with 16" centers) or butted up against a joist. The housing will mount through drywall thickness up to 3/4", with a rough in opening of 14 3/4" x 8 3/8".

• Single Pack Shipping Info

Box Dim: 19" x 10 1/2" x 8 1/8"

UPC: 0-8316229610-8

Shipping Weight: 13 lbs.

PROJECT								ARCHITECT			
LOCATION								ENGINEER			
CONTRACTOR								SUBMITTED BY			
								DATE			
FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: 820 Lincoln Drive
West Chester, Pennsylvania 19380-4466
Tel: (877)-304-3785
Fax: (610) 696-8048

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015